

GS

P2P 720P 16CH AHD DVR

Support AHD/Analogy/IP Camera Triple hybrid

MODEL	NT-D9816C
<b>System</b>	
Main Processor	HI3531
Operating System	Embedded LINUX
<b>Video</b>	
Input	16 Channel, AHD
Output	1HD OUTPUT,1VGA
<b>Audio</b>	
Input	4Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
<b>Alarm</b>	
Input	NO
Output	NO
Motion Detection	16Channel
Trigger Events	Recording, Alarm, Email
Email Alarm	Send Picture to The Designated E-mail
<b>Display</b>	
VGA	Resolution: 1024×768, 1280×720, 1280×1024, 1920×1080
HD OUTPUT	Resolution: 1024×768, 1280×720, 1280×1024, 1920×1080
Display Split	16 Channel / 8 Channel/ 4 Channel/ 1Channel
Privacy Masking	8 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
<b>Recording</b>	
Video Compression	H.264
Audio Compression	G711A
Resolution	720P(1280×720), 960H(P:960×576/N:960×480)
Video Quality	Best/Fine/Normal
Record Rate	AHD 720P(1280×720 100fps), 960H(P:960×576 100fps/N:960×480 120fps) IPC 1080P(1920×1080 100fps) AHD 720P+960H (Total:100 fps) AHD 720P+IPC 720P(Total:100 fps) 960H + IPC 720P(Total:100 fps)
Record Mode	Manual/Timer/Motion Detection/Alarm
<b>Playback &amp; Backup</b>	
Sync Playback	16 Channel /8 Channel /4 Channel/ 1Channel
Remote Playback	16 Channel /8 Channel /4 Channel/ 1Channel
Playback Rate	Total:100fps
Search Mode	Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play
Smart Phone Playback	YES
Backup Mode	USB Device/Network
<b>Network</b>	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	HTTP, IPv4, TCP/IP, DHCP, DNS, DDNS,NTP
DDNS	SODDNS
Web Browser	IE6-11
CMS Software	Support Windows XP /Windows Vista/Windows 7/Windows 8
Smart Phone	Support Window Mobile, iPhone,iPad, Android, and 3G
<b>Hard Disk Driver</b>	
Interface Type	1SATA Interface
Capacity	Up to 4TB Capacity
<b>General</b>	
Language	Japanese, French, Portuguese, Spanish, Traditional Chinese,Polish,Korean, Persian , German,Srpski,Czech, Greek, Arabic,Indonesia,Vietnamese,Romanian,Dutch)
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC12V/3A
Working Environment	-10~55℃/10~90%
Dimension (W×D×H)	335mm×270mm×50mm
Weight	2.3kg (Without HDD)

**Key Feature**

- 4CH 720P real time AHD DVR
- H.264 & Dual-stream video compression
- Support AHD/Analogy/IP Camera Triple hybrid
- Support Both AHD/Analogy cameras with Adaptive Access
- Full Channel@720p resolutions real-time recording
- HD OUTPUT and VGA output at up to 1920x1080p Resolutions
- Long Transmission Distance over coax cable

**Photos****Dimension**