

MODEL	TA04V
System	
Main Processor	HI3520D
Operating System	Embedded LINUX
Video	
Input	4 Channel, AHD
Output	1HD OUTPUT,1VGA
Audio	
Input	1Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
Alarm	
Input	NO
Output	NO
Motion Detection	4Channel
Trigger Events	Recording, Alarm, Email
Email Alarm	Send Picture to The Designated E-mail
Display	
VGA	Resolution: 1024×768, 1280×720, 1280×1024, 1920×1080
HD OUTPUT	Resolution: 1024×768, 1280×720, 1280×1024, 1920×1080
Display Split	4 Channel / 1Channel
Privacy Masking	4 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording	
Video Compression	H.264
Audio Compression	G711A
Resolution	720P(1280×720), 960H(P:960×576/N:960×480)
Video Quality	Best/Fine/Normal
Record Rate	AHD 720P(1280×720 100fps), 960H(P:960×576 100fps/N:960×480 120fps) IPC 1080P(1920×1080 100fps) AHD 720P+960H (Total:100 fps) AHD 720P+IPC 720P(Total:100 fps) 960H + IPC 720P(Total:100 fps)
Record Mode	Manual\Timer\Motion Detection\alarm
Playback & Backup	
Sync Playback	4 Channel / 1Channel
Remote Playback	4 Channel/ 1Channel
Playback Rate	Total:50fps
Search Mode	Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play
Smart Phone Playback	YES
Backup Mode	USB Device/Network
Network	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Network Functions	HTTP, IPv4, TCP/IP, DHCP, DNS, DDNS,NTP
DDNS	SODDNS
Web Browser	IE6-11
CMS Software	Support Windows XP /Windows Vista/Windows 7/Windows 8
Smart Phone	Support Window Mobile, iPhone,iPad, Android, and 3G
Hard Disk Driver	
Interface Type	1SATA Interface
Capacity	Up to 4TB Capacity
General	
Language	Japanese, French, Portuguese, Spanish, Traditional Chinese,Polish,Korean, Persian, German,Srpski,Czech, Greek, Arabic,Indonesia,Vietnamese,Romanian,Dutch)
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC12V/2A
Working Environment	-10~55℃/10~90%
Dimension (W×D×H)	255mm×235mm×45mm
Weight	1.5kg (Without HDD)

Key Feature

- 4CH 720P real time AHD DVR
- H.264 & Dual-stream video compression
- Support AHD/Analogy/IP Camera Triple hybrid
- Support Both AHD/Analogy cameras with Adaptive Access
- Full Channel@720p resolutions real-time recording
- HD OUTPUT and VGA output at up to 1920x1080p Resolutions
- Long Transmission Distance over coax cable

Photos**Dimension**